LA 0712CP M Comfort HC

Air/water heat pump with natural refrigerant and Hydrotower HWK 332HC for heating, cooling and hot water

Experience Better Living.



Environmentally friendly and sustainable
Thanks to the environmentally friendly refrigerant R290 and the high-quality metal housing.

Maximum efficiency with optimum comfort and low noise emissions.
The power-controlled components – compressor, circulation pumps and EC fan – are optimally matched in terms of noise emissions and volume flows.

Perfect for renovation and new construction
Highly efficient: Efficiency class A+++ for low and medium temperature heating systems. When used in conjunction with radiators, the heat pump achieves efficiency values that older heat pumps could only achieve in combination with underfloor heating.

Controlled cooling
In addition to dynamic cooling with fan coil units, intelligent room temperature control with dew point-controlled cooling is also possible (MMH 25 mixed heating circuit module and Smart-RTC+ intelligent room temperature controller included in the package).

Plug'n'play
The combination with the internally installed Hydrotower with buffer and hot water storage tank provides a ready-to-use system hydraulics in the smallest of spaces with hydraulic decoupling of the generator and consumer circuits.

Use of renewable energies
The bivalent renewable operating mode hydraulically integrates heat generators such as wood or thermal solar energy and gives priority to the use of renewable heat.

LA 0712CP M Comfort HC

The reversible LA 0712CP M air-to-water heat pump not only impresses with its natural, environmentally friendly R290 refrigerant, but also with its ability to cover a building heating load of up to 12 kW in a compact housing.
In combination with the Hydrotower HWK 332HC with a 300-litre hot water tank and a 100-litre buffer tank, the system comfortably supplies a 6-person household.
The LA 0712CP M can be used in new buildings as well as in the renovation and replacement of existing systems with a flow temperature of up to 75 °C. In existing buildings with flow temperatures of up to 55 °C, it achieves the highest efficiency class A+++. In new buildings with underfloor heating, the heat pump achieves maximum efficiency values and is ideally suited for single-family homes with an area of up to 200 square metres. In summer, the cooling function with appropriate hydraulics ensures that houses with underfloor heating remain pleasantly cool or, in combination with heat pump radiators, can even cool dynamically. The combination with the internally installed Hydrotower provides a ready-to-use system hydraulic system in the smallest of spaces with hydraulic decoupling of the generator and consumer circuits.

Order code	LA 0712CP M Comfort HC
Item number	383700
LA 0712CP M heat pump	
Energy efficiency class / Energy efficiency (VL 35 °C) / Eta s	A+++ / 211 %
Energy efficiency class / Energy efficiency (VL 55 °C) / Eta s	A+++ / 159 %
SCOP 35 °C / 55 °C	5,35 / 4,06
ERP sound power level	53 dB(A)
Sound power level (A2/Wxx-42; EN14825 part load ratio B)	52,3 dB(A)
Flow temperature	max. 75 °C
Heating capacity / COP (at A-7 / W35) max.*	9,12 kW / 2,75
Heating capacity / COP (at A2 / W35) min.*	4,08 kW / 4,75
Heating capacity / COP (at A7 / W35) min.*	4,65 kW / 5,93
Heating capacity / COP (at A7 / W35) max.	11,61 kW / 4,53
Cooling capacity / EER (at A35/W18) max.*	11,01 kW / 4,48
Lower / upper operating limits (heating mode)	-25 °C / 35 °C
Lower / upper operating limits (hot water)	-25 °C / 46 °C
Refrigerant / refrigerant quantity	R290 / 1,1 kg
Maximum power consumption	15,5 A
Connection voltage	1/N/PE ~230 V (50Hz)
Heat pump dimensions (W x H x D)**	1330 × 1051 × 501 mm
Heat pump weight	156 kg
Hydrotower HWK 332HC	
Energy efficiency class	C
Hydrotower dimensions (W x H x D)**	710 × 1890 × 950 mm
Hydrotower weight	205 kg

* Heating capacity and coefficient of performance (COP) according to EN 14511
** Please note that additional space is required for pipe connections, operation and maintenance

Due to the flammable, natural refrigerant R290, a protection area surrounding the unit must be maintained, depending on the installation location. Further requirements for the installation conditions can be found in the installation and operating instructions available at www.dimplex.eu/LA0712CPM and must be strictly observed.

Zentrale
Glen Dimplex Deutschland GmbH
Geschäftsbereich Heating & Ventilation
Am Goldenen Feld 18
D-95326 Kulmbach

T + 49 9221 709 -101
F + 49 9221 709 -339
info@dimplex.de
www.dimplex.eu